

# The Products (O.E.M.)

## For Plasma Display




Input : 85~264VAC  
 Wattage : 570W with PFC  
 Output : +3.3V/1A, +5V/6A, +5V/1A,  
 +12V/2A, +15V/1A, +65V/1A,  
 +175V/2A, -175V/0.1A, +12V/1.5A  
 Dimension : 340 x 300 x 50 (mm)  
 Efficiency : 84% typical

## For Franking Machine



Input : 90~264VAC  
 Wattage : 83W with PFC  
 Output : +32V/2A, +5.1V/2A,  
 +12V/0.75A  
 Dimension : 205 x 129 x 55 (mm)  
 Efficiency : 85% typical

## For Scanner



Input : 85~264VAC  
 Wattage : 110W  
 Output : +24V/3A, +5V/2.5A, +3.3V/4A,  
 +18V/0.5A, +7.5V/0.5A  
 Dimension : 190 x 150 x 45 (mm)  
 Efficiency : 75%

## For Public Audio Amplifier



Input : 90~264VAC  
 Wattage : 320W with PFC  
 Output : +43V/2A, -43V/2A (Load I)  
 +58V/2.8A, -58V/2.8A (Load II)  
 Dimension : 108 x 190 x 45 (mm)  
 Efficiency : 85%

## For Raid System



Input : 90~264VAC  
 Wattage : 350W with PFC  
 Output : +5V/25A, +12V/40A (total 350W)  
 Dimension : 125 x 303 x 44 (mm)  
 Efficiency : 80%

## For Video System




Input : 90~264VAC  
 Wattage : 100W with active PFC  
 Output : +12.4V/7A, -12.4V/1A  
 Dimension : 243 x 80 x 32 (mm)  
 Efficiency : > 80%

## For Broadcast



Input : 85~265VAC  
 Wattage : 155W with PFC  
 Output : +7.4V/10A, -7.4V/5A  
 Dimension : 100 x 225 x 40 (mm)  
 Efficiency : 74% typical

## For Plotter



Input : 85~264VAC  
 Wattage : 660W  
 Output : +3.3V/14A, +5V/10A, +5V/3A,  
 +12V/2A, +35V/15A  
 Dimension : 300 x 276 x 77 (mm)  
 Efficiency : 81% typical

## For IPC (No Fan)



Input : 85~264VAC  
 Wattage : 170W  
 Output : +5V/10A, +12V/5A, -12V/0.8A,  
 +3.3V/12A, +5Vsb/1.5A  
 Dimension : 85 x 230 x 44 (mm)  
 Efficiency : 75% typical