

軸流ファン Axial Fan

92×92×25mm NEW STYLE



- *Material Impeller & Frame : Plastic (UL 94V-0)
- *Lead Wires : UL 1007AWG # 24 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- *Impeller : 7 Blades
- *Rotational direction CCW view from inlet face
- *Weight : 95g (3.35oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4holes)
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量		风压		噪音
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m ³ /min	CFM	mm Aq	IN Aq	dB-A
DT1209L	B	12	5~13.8	0.07	0.84	1750	0.91	32.00	1.32	0.052	23.2
DT1209M	B	12	5~13.8	0.12	1.44	2200	1.22	43.00	2.05	0.080	27.6
DT1209H	B	12	5~13.8	0.17	2.04	2700	1.49	52.50	3.15	0.124	33.5
DT1209G	B	12	5~13.8	0.25	3.00	3100	1.76	62.00	4.10	0.161	37.0
DT1209U	B	12	5~13.8	0.40	4.80	3500	2.06	73.00	5.05	0.198	39.5

- *Function type is optional
- *The max. air flow and the speed are measured in free air;
max Air pressure is measured at zero air flow.
- *Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- *All readings are typical values at rated voltage.
- *Specifications are subject to change without notice.

