

軸流ファン Axial Fan

120×120×25mm SERIES



- *Material Impeller & Frame : Plastic (UL 94V-0)
- *Lead Wires : UL 1007AWG # 24 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- *Impeller : 7 Blades
- *Rotational direction CCW view from inlet face
- *Weight : 121g (4.26oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4 holes)
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量		风压		噪音
PART NO.	B.S.F	VDC	VDC	Amp	Watt	R.P.M	m3/min	CFM	mm Aq	IN Aq	dB-A
DT1212L	B	12	5~13.8	0.18	2.16	1700	1.81	64.00	1.66	0.065	28.0
DT1212M	B	12	5~13.8	0.23	2.76	2000	2.18	77.00	2.73	0.107	31.0
DT1212H	B	12	5~13.8	0.45	6.00	2300	2.60	92.00	3.61	0.142	34.0

- *Function type is optional
- *The max. air flow and the speed are measured in free air;
max Air pressure is measured at zero air flow.
- *Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- *All readings are typical values at rated voltage.
- *Specifications are subject to change without notice.

