

# 軸流ファン Axial Fan Nidec TALENT TOP

40×40×28mm SERIES



- \*Material Impeller & Frame : Plastic (UL 94V-0)
- \*Lead Wires : UL 1007AWG # 26 or Equivalent  
Red Wire Positive (+)  
Black Wire Negative (-)
- \*Impeller : 5 Blades
- \*Rotational direction CCW view from inlet face
- \*Weight : 46g (1.62oz)

**SPECIFICATION :** B : 2 Ball Bearings S : Sleeve  
N : Nanometer Bearing  
**Frame Type :** P : Flange Type (8 holes)  
T : Rib Type (4 holes)  
Other Specially Design Type

| 型号        | 轴承    | 输入电压 | 电压范围   | 电流   | 功率   | 转速    | 风量                  |       | 风压    |       | 噪音   |
|-----------|-------|------|--------|------|------|-------|---------------------|-------|-------|-------|------|
| PART NO.  | B.S.N | VDC  | VDC    | Amp  | Watt | R.P.M | m <sup>3</sup> /min | CFM   | mm Aq | IN Aq | dB-A |
| DXL1204U  | B     | 12   | 5~13.8 | 0.45 | 5.40 | 14000 | 0.57                | 20.30 | 29.80 | 1.173 | 49.0 |
| DXL1204S1 | B     | 12   | 5~13.8 | 0.69 | 8.28 | 16000 | 0.66                | 23.30 | 33.50 | 1.319 | 53.0 |

\*Function type is optional

\*The max. air flow and the speed are measured in free air,  
max Air pressure is measured at zero air flow.

\*Noise is measured in semi anechoic chamber in free air,  
one meter from intake side.

\*All readings are typical values at rated voltage.

\*Specifications are subject to change without notice.

